

COSMOS PUMPS

TECHNICAL DATASHEET SUBMERSIBLE DEWATERING PUMP MODEL: CDW1206UH

Excellence in Motion

Sr.No	PARTICULAR	
1	MODEL	CDW1206UH
2	MAX. DISCHARGE (lpm)	3475
3	TEMP DEG. C	40°C
4	SHUT OFF HEAD (m)	198
5	WEIGHT (Kg)	1500
6	PUMP B.K.W. (KW)	89.5
7	MOTOR RATING (HP)	120
8	DISCHARGE SIZE	6"
9	SPEED	2900
10	TYPE OF IMPELLER	2-STAGE
11	SEALING	DUAL SiC vs SiC MECHANICAL + OIL SEAL
12	BEARINGS	
	i) BEARING TYPE	BALL BEARING
	ii) BEARING LUBRICATION	GREASE
	iii) BEARING LIFE	20000 - 25000 HRS.*
13	CABLE DETAILS	
	i) TYPE	PVC INSULATED, DOUBLE SHEATHED
	ii) POWER/CONTROL CABLE SIZE	2 NOS x 4 CORE x 35 Sq.mm + 1 NOS x 4 CORE x 1.5 Sq.mm
	iii) LENGTH Mtr	CABLE 20m + 1m STEEL GRIP
14	MATERIAL OF CONSTRUCTION	
	iv) MAKE	COSMOS PUMPS
	i) PUMP / MOTOR BODY	CI FG 300
	ii) STATOR CASING	EXTRUDED ALUMINIUM ALLOY
	iii) IMPELLER	2-STAGE SS316
	iv) SHAFT	SS431
	v) DIFFUSER	NITRILE RUBBER MOULDED
	vi) MECH. SEAL	SiC vs SiC
	vii) HARDWARE, STRAINER	SS304
15	MOTOR DETAILS	
	i) MAKE	COSMOS PUMPS
	ii) RATING	164 A
	iii) No. OF POLES	2
	iv) METHOD OF STARTING	VFD
	v) MOISTURE SENSOR	NO
	vi) ELECTRIC MOTOR TYPE	INDUCTION MOTOR
	vii) CLASS OF INSULATION	H CLASS
	viii) PROTECTION	THERMAL SENSOR IN STATOR
	ix) SPEED	2900
16	STATOR PANEL	
	i) MAKE	COSMOS PUMPS
	ii) PROTECTION RATING	IP62
	iii) AMPERE RATING	AS PER 120 HP VFD PANEL
	iv) SPECIFICATION & FEATURES	CATALOGUE ATTACHED

COSMOS PUMPS PVT LTD

I-23, DLF Industrial Area-I, Faridabad, Haryana-121003 (India).

Tel : +91-99333 22238

E-Mail : cosmos@cosmospumps.com

Website : www.CosmosPumps.com